



File Name: 802c system controller manual.pdf

Size: 4776 KB

Type: PDF, ePub, eBook

Category: Book

Uploaded: 29 May 2019, 15:43 PM

Rating: 4.6/5 from 714 votes.

Status: AVAILABLE

Last checked: 3 Minutes ago!

In order to read or download 802c system controller manual ebook, you need to create a FREE account.

[Download Now!](#)

eBook includes PDF, ePub and Kindle version

[❑ Register a free 1 month Trial Account.](#)

[❑ Download as many books as you like \(Personal use\)](#)

[❑ Cancel the membership at any time if not satisfied.](#)

[❑ Join Over 80000 Happy Readers](#)

Book Descriptions:

We have made it easy for you to find a PDF Ebooks without any digging. And by having access to our ebooks online or by storing it on your computer, you have convenient answers with 802c system controller manual . To get started finding 802c system controller manual , you are right to find our website which has a comprehensive collection of manuals listed.

Our library is the biggest of these that have literally hundreds of thousands of different products represented.



Book Descriptions:

802c system controller manual

Lastmanuals provides you a fast and easy access to the user manual BOSE 802C II. We hope that this BOSE 802C II user guide will be useful to you. General Description. The Bose 802 Series II sound components provide a fully modular system designed for high quality reinforcement of voice and music. Bose 802 Series II loudspeakers work with the 802 C Series II systems controller for active equalization of the system. Bose Corporation, Framingham 01701, Mass, U. S. A. Made in Germany. Serial No. Figure 1. Beamwidth vs Frequency Bose 802II. The loudspeaker shall be provided with a ducted vent system, tuned at 55Hz. The loudspeaker enclosure of the 802 Series II loudspeaker shall be composed of micareinforced polyethylene copolymer structural foam. The loudspeaker system shall be supplied with a separate systems controller, to be connected before the inputs of the system power amplifiers. The fixed, 2channel systems controller shall provide active electronic equalization and crossover functions. It shall include an operating mode switch, input sensitivity switch, lowfrequency output level control, and mono sum switch. The systems controller shall use screwtype terminal strips for balanced input and output wiring connections. The electronic controller shall be the Bose 802 C Series II systems controller. Systems Controller Technical Information. The power handling capacity of. Product C E is compliant for EM C and Safety. Warranty Information. The Bose 802 Series II loudspeaker is covered by a 5year, transferable limited warranty. The Bose 802 C Series II systems controller is covered by a 2year, transferable limited warranty. Figure 3a. Figure 3b. In any way cant Lastmanuals be held responsible if the document you are looking for is not available, incomplete, in a different language than yours, or if the model or language do not match the description. Lastmanuals, for instance, does not offer a translation service. <http://xn--80adpfaaeictf0c6c7i.xn--p1ai/public/calculator-manual-ti-30x-iis.xml>

- **802c system controller manual, bose 802c system controller manual, bose 802c ii system controller manual, bose 802c system controller service manual, bose 802c-ii system controller user manual, bose 802c ii system controller service manual, 802c system controller manual, 802c system controller manual pdf, 802c system controller manual download, 802c system controller manual free, 802c system controller manual online, bose 802c ii system controller manual, bose 802c system controller manual.**

Learn more opens in a new window or tab This amount is subject to change until you make payment. For additional information, see the Global Shipping Programme terms and conditions opens in a new window or tab This amount is subject to change until you make payment. If you reside in an EU member state besides UK, import VAT on this purchase is not recoverable. For additional information, see the Global Shipping Programme terms and conditions opens in a new window or tab Estimated delivery dates opens in a new window or tab include sellers dispatch time, and will depend on postal service selected. Delivery times may vary, especially during peak periods. Learn More opens in a new window or tab Learn More opens in a new window or tab Learn More opens in a new window or tab Learn More opens in a new window or tab Learn More opens in a new window or tab See the sellers listing for full details. You're covered by the eBay Money Back Guarantee if you receive an item that is not as described in the listing. Find out more about your rights as a buyer opens in a new window or tab and exceptions opens in a new window or tab. Contact the seller opens in a new window or tab and request a postage method to your location. Please enter a valid postcode. Please enter a number less than or equal to 1. We may receive commission if your application for credit is successful. Terms and conditions apply. Subject to credit approval. We may

receive commission if your application for credit is successful. All Rights Reserved. User Agreement, Privacy, Cookies and AdChoice Norton Secured powered by Verisign. Discover everything Scribd has to offer, including books and audiobooks from major publishers. Browse Books Site Directory Site Language English Change Language English Change Language. Page 3 SAFETY INFORMATION 1. Parts that have special safety characteristics are identified by the symbol on schematics or by special notes on the parts list. <http://alansh.com/pic/calculator-hp-50g-manual.xml>

Use only replacement parts that have critical characteristics recommended by the manufacturer. 2. Make leakage current or resistance measurements to determine that exposed parts are acceptably insulated from the supply circuit before returning the unit to the customer. Use the following checks to perform these measurements A. Page 4 ELECTROSTATIC DISCHARGE SENSITIVE ESDS DEVICE HANDLING This unit contains ESDS devices. Handle boards by the edges only. Unbalanced input, 42k. The 802C system controller automatically selects the proper crossover function and equalization curve for a given system application through use of a switching network operating in conjunction with the units output jacks. You must test all modes of the 802C to assure proper operation. Frequency 55Hz 750Hz 15kHz 1.2 Perform the test below to verify that the mode select operation is working properly. Approval from the Field Service Manager is required before ordering. 2. The individual parts located on the PCB are listed in the Electrical Part List. 3. This part is critical for safety purposes. Failure to use a substitute replacement with the same safety characteristics as the recommended replacement part might create shock, fire and or other hazards. 4. RC4156 is to be used ONLY as a replacement for U5 and U6. However it is possible to convert a 110 Volt unit by replacing the transformer and a 220 Volt European unit. 1. 220 Volt to 110 Volt Conversion 2. 110 Volt to 220 Volt Conversion Note Conversions must be performed with the line cord disconnected from any power source. Refer to Figure 3 below for the following procedures. Units with serial numbers beginning with 200000 are the new SMD 802Cs. Contents. Safety Information. 3. Electrostatic Discharge Sensitive ESDS Device Handling. 4. Specifications. 5. Technical Description. 6. Figure 1. Locking Tab Screw Location. 7. Figure 2. Original 802C PCB Exploded View. 8. Figure 3. SMD 802C PCB Exploded View. 8. Test Procedures. 910. Part List Notes.

11. Main Part List. 12. Figure 4. Main Parts Exploded View. 13. Electrical Part List. 1417. Voltage Conversion Instructions. 18. Figure 5. Voltage Conversion Diagram. 18. Figure 6. Top Cover Connection Diagram. 19 Start Free Download. Be sure to check that it is the user manual to exactly the device that you are looking for. In our database Bose 802c it belongs to the category Network Card. A user manualBose 802c is taken from the manufacturer, a Bose company it is an official document, so if you have any doubts as to its contents, please contact the manufacturer of the device Bose 802c directly. You can view the user manualBose 802c directly online or save and store it on your computer. In addition to signal routing based on equalization require The front panel The 802C system controller retains the If you have any questions, you can ask them in the form below. Other users viewing this website will have the opportunity to help you solve your problem with Bose 802c. Remember that you can also share the solution. If you solved the problem yourself, please write the solution to the problem with Bose 802c you will surely help many users by doing so. Ask a question our users can help you. The loudspeakers work well but Im aware that I should use the 802c to equalize the sound. My problem is that Im not sure how to connect the 802c with the powered mixer, since I figure it would usually be used with a separate mixer and amp. The powered mixer is a 12channel SoundLab PMX1252D. Theres no manual and its so old I cant find one online either. Does anyone know if the 802c can be connected without blowing anything up. You will probably only use ONE channel on the Bose Controller. You can also find the user guide for the controller online. there may be other settings on it you need If you shot a better, tighter picture isolating just the upper right hand corner of your mixer so we can read the labels on the inputs and outputs we may be able to be more specific.

<http://www.drupalitalia.org/node/77276>

So you need to get a mixer without outputs amplified ! Plug a signal into one channel, set the Effects Send knob for that channel somewhat midpoint, take the EFX output to a guitar amp or somesuch. Then when you change that channels fader, does the output of the Effects Send change. If so, youre in business. Set the Effects Send for every channel you use to a similar spot, take the EFX Output to the input of the controller, return the output of the controller to the Aux In. So your channel faders will balance the channels and the Aux Input control and maybe the main faders will set the overall volume. The WORST case would be to get a nice, clean inexpensive mixer. How many vocals, instruments are you likely to need to mix. See the photo of the top of the unit for details. Items must be returned in original, asshipped condition with all original packaging. Please check the fields highlighted in red. Currency. Something went wrong. View cart for details. All Rights Reserved. Please check your inbox, and if you can't find it, check your spam folder to make sure it didnt end up there. Please also check your spam folder. Use only replacement parts that have critical characteristics recommended by the manufacturer. Use the following checks to perform these measurements With the unit AC switch first in the ON position, then in the OFF position, measure from a known earth ground metal water pipe, conduit, etc. to all exposed metal parts of the unit antennas, handle bracket, metal cabinet, screwheads, metallic overlays, control shafts, etc., especially any exposed metal parts that offer an electrical return path to the chassis. Any current measured must not exceed 0.5 milliamp. Reverse the unit power cord plug in the outlet and repeat test. When the exposed metallic part has a return path to the chassis, the reading should be between 1 and 5.2 Megohms. When there is no return path to the chassis, the reading must be "infinite".

<https://elsenorcafe.com/images/bostitch-6-gallon-air-compressor-owners-manual.pdf>

If it is not within the limits specified, there is the possibility of a shock hazard, and the unit must be repaired and rechecked before it is returned to the customer. We recommend the following precautions when repairing, replacing or transporting ESDS devices. Do not insert unprotected devices into materials such as plastic, polystyrene foam, clear plastic bags, bubble wrap or plastic trays. In addition to signal routing based on equalization requirements, the switching network indicates mode of operation on its front panel. The front panel also includes highcut and lowcut switches which decrease line output by 4dB at 55Hz and by 10dB at 16kHz. Sharp subsonic and ultrasonic bandlimiting filters reduce power waste, stage noise, highfrequency instability, and interference. This manual will identify the different procedures, PCB layouts, and components where necessary. Weve just launched a dedicated AudioMart in Russia, UK Audio Mart. For details please read this FAQ entry. Dr. Boses design was effective in reducing the hot spot that can cause feedback problems with live events and the EQ unit is an essential part of the speaker design, else the frequency response will be anything but flat. The Bose Controller equalizes the speakers for optimum sound quality, and also provides a flexible crossover. In addition to signal routing based on equalization requirements, the switching network indicates mode of operation on its front panel. The front panel also includes highcut and lowcut switches which decrease line output by 4dB at 55Hz and by 10dB at 16kHz. Sharp subsonic and ultrasonic bandlimiting filters reduce power waste, stage noise, highfrequency instability, and interference. Unit has rack wear but is otherwise in ok condition no box so prefer local sale, could ship if buyer pays. Please do not offer the downloaded file for sell only use it for personal usage. Looking for other manual For this no need registration. May be help you to repair.

<http://emadjoe.com/images/bostitch-6-gallon-air-compressor-user-manual.pdf>

You could suffer a fatal electrical shock. Instead, contact your nearest service center. Note! To open downloaded files you need acrobat reader or similar pdf reader program. In addition, Also some files are djvu so you need djvu viewer to open them. These free programs can be found on this page

needed progs If you use opera you have to disable opera turbo function to download file. If you cannot download this file, try it with CHROME or FIREFOX browser. Translate this page Relevant AUDIO forum topics Bose Sounddock 1 tapegyseg csati Sziasztok. Egy barátom megkért, hogy találjak vagy gyartsak egy tapegyseget a Bose dokkolojához. Sajnos az eredetiket aranyarban adják, így gyartanom kell egyet. Találtam is egy elegáns kis 4 pines csatit, de fennakadtam az eredeti csatlakozó labkiosztasan. Találtam egy rajzot de nem tudom eldönteni, hogy a kábelén levő ábrázolja, vagy a dokkolóban levő. Ha valakinek dolga volt ilyennel, és tudna segíteni, kérem ne tartsa vissza magát. Köszönöm.. Bose Lifestyle CD20 FLC kijelző halvány Sziasztok! A fenti készüléknek halvány a kijelzése. Eleg érdekesen van megoldva a kijelző tápfesz, sokban függ a bejövő 12VAC feszültségtől. Kérdésem az lenne, hogy a fűtest próbáljam emelni, vagy a 24Vot. A D8on a 30V is kevesebb, de az AC 4.5V is. Melyik befolyásolja jobban a fényerőt. A fűtes, vagy a negatív tápfesz Udv Jacint BOSE bekötési rajz Legyszi legyszi ha valaki tudnasegíteni egy BOSE AMP2440as erosito bekoteseben, azt nagyon szepen megkoszonem. Ez AUDI A3asbol van, a stecker nincs meg. Basszus vegfoka 23mp mulva megfut vagy pozitivba vagy negativba ha nincs a hangszoró rarakva, hangszoróval azonnal letilt, amikor a kimeneten eljut DC 4Vig a védelem lekapcsolja relev az erositot.

Mikor a MUTE hibát kerestem, volt olyan eset is, hogy nem futott meg a kimenet és szólt a basszus rendesen, de újbóli bekapcsoláskor ha nem halkítottam le a potit akkor kikapcsolt a relé, ha lehalkítottam akkor jó lett, de nagyon susogott, arra hasonlított mint amikor FM radio nincs az allomason, van egy közös mute tranzisztor az kapcsolja az összes többi, ha azt kismézttem akkor is megmaradt a susogás, szerintem visszafelé jött valamelyik oldalról ezért szedtem ki mindegyik oldalról a tranzisztorokat, nem akartam bajlódni vele, hogy honnet jön a susogás vissza. Mi lehet a gond Similar manuals You can write in English language into the forum not only in Hungarian. Sharp subsonic andultrasonic bandlimiting filters reducepower waste, stage noise, highfrequencyinstability, and interference. Thedrivers feature lowimpedance,edgewound aluminum voice coils,12ounce Ferrite V ceramic magnets, andmolded polyester frames. Their advancedcone and motor system give them highlinear excursion capability and poweroutput.Tuned reactive air columns reducedistortion by controlling the coneexcursion required to reproduce deep bassfrequencies. A builtin directivity controlcircuit maintains the vertical dispersionpattern through the highfrequency range.It also protects the drivers fromhighfrequency overload.The 802C Series II systems controller is asinglerack sized device. It also provides automatic outputmuting on turnoff, and a securerearpanel operating mode switch. Page 2 REFER TO YOUR INSTRUCTION MANUAL FO Thank you, for helping us keep this platform clean. The editors will have a look at it as soon as possible. Id start by just going XLRXLR into 1 amp and seeing if that works. Then jump directly into the other amp using the link out on the amp. See page 14 of the manual. Something went wrong.Learn more opens in a new window or tab Read item description or contact seller for postage options. This amount is subject to change until you make payment.

For additional information, see the Global Shipping Program terms and conditions opens in a new window or tab This amount is subject to change until you make payment. For additional information, see the Global Shipping Program terms and conditions opens in a new window or tab Learn more opens in a new window or tab Learn more opens in a new window or tab Learn more opens in a new window or tab Learn more opens in a new window or tab See the sellers listing for full details. Contact the seller opens in a new window or tab and request a postage method to your location. Please enter a valid postcode. Please enter a number less than or equal to 25. If you don't follow our item condition policy for returns, you may not receive a full refund. Refunds by law In Australia, consumers have a legal right to obtain a refund from a business if the goods purchased are faulty, not fit for purpose or don't match the seller's description. More information at returns. All Rights Reserved. Looks like "Bose 802c system controller" has already been sold. Check out some similar items below. Bose L1 model 1s powerstand. Bose B1 Bass Module

brand new. Used many times for live performances. Still sound sthe same and now has a brand new bass.Remote control. Manual. Everything in the picture. In full working order. Excellent working condition Bose Sound System 160.00 1 x Bose Acoustimass 5 series iiiIn perfect working order I can say nothing bad to that system only that's it has amazing loud sound. Some marks on them as you can see on the pictures. For any more information or pictures don't hesitate to contact. Bose home system 235.00 Fully working. Honestly it sounds amazingDVD player. SubwooferAnd stands. I have all the he cables and remote for it Bose home sound system 50.00 Bose home system sold as seen comes with remote but dont have wires or cables but can be got sold as seen Bose system with remote 50.00 Bose system with remote.

Sound is very good, Excellent condition. Hardly been used. As New. Collection only please Bose wave music system 200.00 Here is Bose wave music system with all accessories. Working perfectly! Collection onlyOther attachments included. New like Bose iPhone Speaker System 50.00 Excellent condition hardly used. Collection Woodford Green Dj system controller 1,100.00 Full PA sytem pioneer controller, cordless mic, FBT 1000w satellite system amico, mic stand, eq, ikey audio digital recording, reloop. Bose 321 home theater system 185.00 The Bose 321 Series II Home Theatre System is a 2.1 channel surround sound system with the Dolby Digital decoder to deliver rich and detailed sound. It has two compact speakers, a subwoofer and a DVD player with an FM tuner. This system supports playable formats such as the CD, CDR, CDRW, DVD and DVDAudio. Super sound quality. With all the wires. Optical cable support. Every thing is in good working order. MRI Multi Room Interface plus P1 remote and 6 CD changer. In perfect working condition. Selling due to need cash. Can be shown in working condition prior to collection. Comes with 2 original Bose wall brackets. Please see photos for description. If you have any further questions please feel free to contact me. Condition is Used. Prefer Collection because I wont be responsible if it gets damaged during shipping. Im open to sensible offers. Sound System 4000W BOSE F1 2,100.00 The Bose F1 sound system consists of two active F1 812 speakers and two. F1 subwoofers. It offers flexibility and sound quality in a portable PA The F1 model 812 has a power of F1 subwoofer also has a power of 1000 watts in a compact and easy to Sound Activated. Music Sensitivity. Speed Controls. Comes with correct Bose connecting cables themselves very expensive, Bose transformer power unit, power lead for sub, and instructions. Speakers are Sony, Right Front, Left Front, Centre, Surround Rear Left and Surround Rear Right. All are labelled.

Everthing is fully working. Fantastic bass adjustable from the powered subwoofer gives superb full home cinema 5.1 surround, Bose Cinemate 15 Home Cinema System 345.00 PreOwned Bose Cinemate 15 Home Cinema System in good condition. Comes boxed, complete with the sub, soundbar, remote control and all cables. Full, impressive TV sound that spreads well beyond the soundbar itself deep bass from the acoustic mass module that brings movies, TV shows, sports and video games to life The soundbar fits easily in front of TV and connects with just one cable. Easytouse universal remote controls TV, and more. Bose Solo 5 TV Sound System 95.00 Fully working and in great condition. Comes with universal remote control, power cord and optical digital audio cable. Collection preferred but delivery is also available. Bose SoundTouch 130 home cinema system 600.00 Originally bought for 1500. In perfect working order. It comes with power cable only. Remote can be purchase for as little as 6 with fast and free delivery. Preowned. Used Condition. Price 139 plus 5.99 postage. Brand Bose. Model AWRC3PIncludes all cords. Reduced to 150 OBO Sold item Switch to the previous item image Switch to the next item image Description system controller for use with bose speaker system 50 ono system controller for use with bose speaker system 50 ono. Shpock is a marketplace and classifieds platform that brings millions of private buyers and sellers across the United Kingdom together London, Brighton, Birmingham, Bristol, Manchester, Leicester and Liverpool are amongst the most active areas for second hand shopping.

<http://www.drupalitalia.org/node/77277>